



Product data sheet

HLAY5BD21

Characteristics

Selector switch, HLAY5, 1NO, 2 positions 45°, stay put, standard handle, black



Main

Range of product	HLAY5
Device presentation	Complete product
Product or component type	Selector switch
Bezel material	Metal
Mounting diameter	22 mm
Head type	Standard

Complementary

Fixing collar material	Metal
Cap/operator or lens colour	Black
Shape of signaling unit head	Round
Type of operator	Stay put
Operator profile	Black standard handle
Operator position information	2 positions 45°
Contacts type and composition	1 NO
Contact operation	Slow-break
Contacts usage	Standard contacts
Mechanical durability	100000 cycles
Connections - terminals	Screw clamp terminals
[Ith] conventional free air thermal current	6 A
[Uimp] rated impulse withstand voltage	6 kV
[Ie] rated operational current	2 A at 380 V 3.3 A at 220 V, AC-15 0.5 A at 220 V 1.1 A at 110 V, DC-13
Electrical durability	50000 cycles

Environment

Ambient air temperature for operation	-5...40 °C
Standards	IEC 60947-5-1

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.