



Product data sheet

HDKUS5024

Characteristics

Switch mode power supply, HDKUS, 50 W, 24 V



Main

Range of product	HDK
Product or component type	Power supply

Complementary

Rated power in W	50 W
Input voltage	100...264 V AC single phase
Network frequency	47...63 Hz
Output voltage	24 V DC
Output voltage tolerance	
Line and load regulation	
Residual ripple	
Output protection type	Against overvoltage, protection technology: tripping if $U > 1.5 \times U_n$
Connections - terminals	For input connection: screw terminals
Operating position	Any position

Environment

Standards	UL 60950-1 EN 60950-1 EN 60335-1 EN 61558-1 EN 61558-2-16
Product certifications	CE
Operating altitude	2000 m
Ambient air temperature for operation	-10...60 °C (with derating factor)
Ambient air temperature for storage	-30...70 °C
Relative humidity	20...90 %
Dielectric strength	4000 V between input and output

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Himel nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.